



Product Specification

Pak-Man H-60



Updated 3/31/08

Description

Pak-Man H-60 is a medium to heavy-duty grade, reinforced water activated tape. The product is available in natural and white.

Construction

Papers

Top Sheet: 23 lbs/ream Natural or 30 lbs/ream White High Strength Virgin Kraft

Bottom Sheet: 23 lbs/ream MG Natural High Strength Virgin Kraft

Laminant

Non-Asphaltic Polypropylene based polymer laminant

Non-Staining, Flexible, Water Resistant, Complies with FDA; CFR 175.105

Reinforcement

3-Way Fiberglass Reinforcing Pattern

Pattern: Lengthwise threads with diamond cross-machine pattern

Lengthwise Threads: 75 Denier Fiberglass – 19/32" spacing (2-1-1-1-2)

Cross-Machine Threads: 150 Denier Fiberglass – Diamond Pattern
less than 1¼" spacing between threads

Adhesive

Smooth, even coating of special high tack, water-activated, modified cornstarch based adhesive

Caliper

5.9 Mills to 6.9 Mills

Recommended Application

Pak-Man H-60 is recommended for sealing medium to heavy weight cartons up to 40 lbs.

Sizes & Put-ups

Pak-Man H-60

Sizes	Rolls/Carton	Cartons/Pallet
2½" x 450'	12	60
3" X 375'	8	75
3" x 450'	10	60
3" x 500'	6	90/105
3" x 500'	10	60
3" x 600'	10	60

Please call our sales service department for custom sizes and put-ups