



Product Specification

All Purpose Box Tape

Description

All Purpose Box Tape is used as a joint tape for corrugated boxes. The product is available in natural and white.

Construction

Papers

Top Sheet: 35 lbs / ream Natural or White High Strength Kraft

Bottom Sheet: 40 lbs / ream Natural High Strength Kraft

Laminating Adhesive

Non-Asphaltic Polypropylene based polymer

Non-Staining, Flexible, Water Resistant, Complies with FDA; CFR 175.105

Reinforcement

Cross Machine Fiberglass Reinforcing Pattern

Pattern: Diamond cross-machine pattern

Cross-Machine Threads: G75 Fiberglass – Diamond Pattern

Adhesive

Smooth, even coating of special high tack, water-activated, modified cornstarch based adhesive

Caliper

8.8 to 10.7 mils

Performance

| Tensile Strength* (CD) | For Cartons with Burst Strength of: | For Boxes with Gross Weight of: |
|---------------------------|--|------------------------------------|
| 60 lb/in | 200 – 275 psi | 65 – 90 lbs |

*Nominal values shown.

Construction and properties such as tensile strength may vary slightly for white box tape products.

Sizes & Put-ups

All Purpose Box Tape

| Sizes | Rolls/Carton | Cartons/Pallet |
|--------------|--------------|----------------|
| 2" x 3400' | 3 | 24 |
| 2.5" x 3400' | 2 | 24 |
| 3" x 3400' | 2 | 24 |

Please call our Customer Service Department for custom sizes and put-ups

While the information, data and recommendations set forth herein are believed to be accurate, Holland Manufacturing Company, Inc. makes no warranty with respect to completeness or accuracy thereto and disclaims all liability from reliance thereon. Persons utilizing this information will make their own determination as to the product's suitability for their purposes prior to use. Holland Manufacturing reserves the right to make changes to our products and related information without notice or obligation and does not warrant the accuracy or timeliness of the materials on this site and has no liability for any errors or omissions in the materials.