

H-40

Product Information Guide

Adhesive Side

Reinforced Water Activated Tape



H-40 Reinforced WAT Specs

Color: Natural Kraft

Duty: Medium

Paper Basis Weight: 23 lb. / 23 lb.

Reinforcement: MD:(1-1-1-1) H75

CD: 1.25" Pattern G150

100% Fiberglass


Product Classification: Reinforced Water Activated Tape – Medium Duty Grade

Intended Use: Closure of Corrugated Boxes – works well on recycled and virgin fiber corrugated boxes. Not intended closure solution for wax coated, clay coated or plastic boxes.

Primary Components: Virgin Kraft Paper, Fiberglass Reinforcement, Starch Based Adhesive, PP Based Laminate


Application Instructions: Use a dedicated water activated tape dispenser with clean brushes and water temperature of 110°F to dispense tape. Apply tape to the corrugate box by applying steady pressure in an outward motion from the middle of the box extending 3"+ down the side panels of the box.

Storage Guidelines: Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is guaranteed for 1 year from date of purchase.



Up to 40 lbs

Typical Width



72mm

**Kraft
Color
Only**



Standard Product Sizes and Put Ups

Item No.	Width x Length	Rolls Per Case	Cases Per Pallet	Stock Item
H4072X375	72mm x 375 LF	8	105	NO
H4072X450	72mm x 450 LF	10	63	YES
H4072X500	72mm x 500 LF	6	90	YES
H4072X600	72mm x 600 LF	10	60	NO
H4072X1000	72mm x 1000 LF	6	48	NO
H4072X6000	72mm x 6000 LF	Printable Roll	68	NO

Custom sizes may be available, consult your Holland sales representative for more information.

Compliance Statement: Holland does not test products for the substances identified in PFAS regulations. Based on information provided by raw material suppliers and internal process evaluation, Holland's WAT products do not contain, as intentionally added ingredients, substances identified in PFAS regulations.



Holland Manufacturing Company

Succasunna, NJ – Corporate HQ

www.hollandmfg.com 973-584-8141