

H-50

Product Information Guide



H-50 Reinforced WAT Specs

Color: Natural Kraft

Duty: Medium

Paper Basis Weight: 23 lb. / 23 lb.

Reinforcement: MD:(1-1-1-1-1) H75

CD: 1.25" Pattern G150

100% Fiberglass


Product Classification: Reinforced Water Activated Tape – Medium Duty Grade

Intended Use: Closure of Corrugated Boxes – works well on recycled and virgin fiber corrugated boxes. Not intended closure solution for wax coated, clay coated or plastic boxes.

Primary Components: Virgin Kraft Paper, Fiberglass Reinforcement, Starch Based Adhesive, PP Based Laminate

Application Instructions: Use a dedicated water activated tape dispenser with clean brushes and water temperature of 110°F to dispense tape. Apply tape to the corrugate box by applying steady pressure in an outward motion from the middle of the box extending 3"+ down the side panels of the box.

Storage Guidelines: Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is guaranteed for 1 year from date of purchase.



Standard Product Sizes and Put Ups

Item No.	Width x Length	Rolls Per Case	Cases Per Pallet	Stock Item
H503X375	3 IN x 375 LF	8	84	NO
H503X450	3 IN x 450 LF	10	63	YES
H503X1000	3 IN x 1000 LF	6	48	NO
H503X6000	3 IN x 6000 LF	Printable Roll	64	NO

Custom sizes may be available, consult your Holland sales representative for more information.

Compliance Statement: Holland does not test products for the substances identified in PFAS regulations. Based on information provided by raw material suppliers and internal process evaluation, Holland's WAT products do not contain, as intentionally added ingredients, substances identified in PFAS regulations.



Holland Manufacturing Company

Succasunna, NJ – Corporate HQ

www.hollandmfg.com 973-584-8141