

Product Information Guide

All Purpose Corrugated Box Tape

Color: Natural

Duty: Heavy

Paper Basis Weight: 2 – 40lb Kraft Virgin Sheets

Reinforcement: Yes, G75 Fiberglass - 0.75 IN CD Pattern

Recyclable: YES



Product Classification: Reinforced Corrugated Box Maker’s Tape

Intended Use: Joint sealing of corrugated boxes.

Primary Components: Kraft Paper, Fiberglass Reinforcement & Water Activated Adhesive

Application Instructions: Use a dedicated water activated tape dispenser with clean brushes and water temperature of 110°F to dispense tape. Apply tape to the corrugate box by applying steady pressure.

Storage Guidelines: Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is guaranteed for 1 year from date of purchase.



Standard Product Sizes and Put Ups					
Item No.	Color	Width x Length	Rolls Per Case	Cases Per Pallet	Stock Item
AP3x3300	Natural	3 IN x 3300 LF	2	24	YES
Custom sizes may be available, consult your Holland sales representative for more information.					

Compliance Statement: Holland does not test products for the substances identified in PFAS regulations. Based on information provided by raw material suppliers and internal process evaluation, Holland’s heat seal stay tape products do not contain, as intentionally added ingredients, substances identified in PFAS regulations.



Holland Manufacturing Company
 Succasunna, NJ – Corporate HQ
www.hollandmfg.com 973-584-8141