



Product Information Guide

Non-Reinforced WAT Specs



Color: Natural or White
Duty: Light, Medium, Heavy
Paper Basis Weight: 40 lb, 60 lb, 90 lb
Reinforcement: None
Recyclable: YES



Product Classification: Non-Reinforced Water Activated Tape

Intended Use: Closure of Corrugated Boxes – works well on recycled and virgin fiber corrugated boxes. Not intended closure solution for wax coated, clay coated or plastic boxes. Light Duty version is intended for banding applications.

Primary Components: Virgin Kraft Paper & Starch Based Adhesive

Application Instructions: Use a dedicated water activated tape dispenser with clean brushes and water temperature of 110°F to dispense tape. Apply tape to the corrugate box by applying steady pressure in an outward motion from the middle of the box extending 3”+ down the side panels of the box.

Storage Guidelines: Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is guaranteed for 1 year from date of purchase.



Standard Product Sizes and Put Ups				
Item No.	Width x Length	Rolls Per Case	Cases Per Pallet	Stock Item
LD1.5X500	1.5 IN x 500 LF	20	84	YES
MD3X600	3 IN x 600 LF	10	60	YES
MDW3X600 (White)	3 IN x 600 LF	10	60	YES
HD3X375	3 IN x 375 LF	10	60	NO
Custom sizes may be available, consult your Holland sales representative for more information.				

Compliance Statement: Holland does not test products for the substances identified in PFAS regulations. Based on information provided by raw material suppliers and internal process evaluation, Holland’s WAT products do not contain, as intentionally added ingredients, substances identified in PFAS regulations.



Holland Manufacturing Company
 Succasunna, NJ – Corporate HQ
www.hollandmfg.com 973-584-8141