

## Product Information Guide



### Heavy Duty Heat Seal Stay Tape

**Color:** Natural or White

**Duty:** Heavy

**Paper Basis Weight:** 90 lb(White) 97 lb (Nat)

**Reinforcement:** None

**Recyclable:** YES


**Product Classification:** Non-Reinforced, Heavy Duty Heat Seal Stay Tape

**Intended Use:** Joint sealing of set-up paperboard boxes.

**Primary Components:** Kraft Paper & Water Based, Heat Activated Adhesive


**Application Instructions:** Use a dedicated heat seal box folding machine. Recommended minimum heat seal operating temperature of 300°F, 30 psi of pressure and 1-2 seconds of dwell.

**Storage Guidelines:** Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is guaranteed for 1 year from date of purchase.



**Set Up Box**

**Typical Width**



**7/8 IN**

**Kraft  
Or  
White**



### Standard Product Sizes and Put Ups

Item No.	Color	Width x Length	Rolls Per Case	Cases Per Pallet	Stock Item
520W	Natural	0.75 IN x 650 LF	38	40	NO
521W	Natural	0.875 IN x 650 LF	32	40	YES
606W	Natural	0.875 IN x 1550 LF	12	45	YES
555W	White	0.75 IN x 575 LF	38	40	NO
556W	White	0.875 IN x 575 LF	32	40	YES
608W	White	0.875 IN x 1400 LF	12	45	NO

Custom sizes may be available, consult your Holland sales representative for more information.

**Compliance Statement:** Holland does not test products for the substances identified in PFAS regulations. Based on information provided by raw material suppliers and internal process evaluation, Holland's heat seal stay tape products do not contain, as intentionally added ingredients, substances identified in PFAS regulations.



**Holland Manufacturing Company**

Succasunna, NJ – Corporate HQ

www.hollandmfg.com 973-584-8141