

Product Information Guide



Medium Duty Heat Seal Stay Tape

Color: Natural or White

Duty: Medium

Paper Basis Weight: 60 lb(White) 65 lb (Nat)

Reinforcement: None

Recyclable: YES


Product Classification: Non-Reinforced, Medium Duty Heat Seal Stay Tape

Intended Use: Joint sealing of set-up paperboard boxes.

Primary Components: Kraft Paper & Water Based, Heat Activated Adhesive


Application Instructions: Use a dedicated heat seal box folding machine. Recommended minimum heat seal operating temperature of 300°F, 30 psi of pressure and 1-2 seconds of dwell.

Storage Guidelines: Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is guaranteed for 1 year from date of purchase.



Set Up Box

Typical Width



7/8 IN

**Kraft
Or
White**



Standard Product Sizes and Put Ups

Item No.	Color	Width x Length	Rolls Per Case	Cases Per Pallet	Stock Item
511W	Natural	0.75 IN x 900 LF	38	40	NO
512W	Natural	0.875 IN x 900 LF	32	40	YES
609W	Natural	0.875 IN x 2150 LF	12	45	NO
553W	White	0.75 IN x 1020 LF	38	40	NO
554W	White	0.875 IN x 1020 LF	32	40	NO
852W	White	0.875 IN x 2550 LF	12	45	NO

Custom sizes may be available, consult your Holland sales representative for more information.

Compliance Statement: Holland does not test products for the substances identified in PFAS regulations. Based on information provided by raw material suppliers and internal process evaluation, Holland's heat seal stay tape products do not contain, as intentionally added ingredients, substances identified in PFAS regulations.



Holland Manufacturing Company

Succasunna, NJ – Corporate HQ

www.hollandmfg.com 973-584-8141