

# BLUE SHIELD 3030

UNDERLAYMENT FOR WOOD AND TILE FLOORING  
VAPOR CONTROL  
INDUSTRIAL WRAP



<b>Color:</b>	Natural
<b>Style:</b>	Grade B, Semi-Permeable Class II Laminated Paper
<b>Paper:</b>	30 lb. / 30 lb. Kraft
<b>Laminate:</b>	30 lb. High-Grade Low Oder Laminating Asphalt
<b>Caliper:</b>	7.0 mils
<b>Tear Str:</b>	MD 179 gf CD 155 gf
<b>Tensile Str:</b>	MD 55 lb/in CD 23 lb/in
<b>Permeability:</b>	(WVTR), 3.2 perms/22.1 g/day/m <sup>2</sup>

*Complete specifications, physical properties, and applicable standards in TDS*

Blue Shield 3030 is a versatile and cost-effective solution for protecting interiors against moisture damage. It excels in wood flooring and tile applications, while also serving as a slip sheet to reduce dust and noise. This exceptional moisture vapor retarder safeguards surfaces from potential issues and enhances their lifespan and appearance. Available in various sizes, Blue Shield 3030 is designed to cater to a wide range of applications, making it an excellent multi-functional product for your construction, renovation, and industrial wrapping applications.

#### Product Classification:

Semi-permeable Grade B, Class II vapor retardant, laminated paper.

#### Intended Use:

Underlayment for wood and tile flooring, industrial wrapping, and barrier applications.

#### Primary Components:

Kraft Paper, Laminating Asphalt

#### Installation Instructions:

**For wood flooring installation:** Holland recommends following the “Wood Flooring Installation Guidelines” published by NWFA and prevailing local building codes. Proper preparation of the installation area is critical including assurance that the subfloor is dry, level, free of debris and tested for moisture level. Blue Shield 3030 is not suitable as underlayment for basement or over crawl spaces without additional moisture mitigation steps.

**For tile installation:** Holland recommends following ANSI A108. 3030 is not a water proof membrane and should not be used in tile applications requiring water proof barriers such as showers or other high moisture areas.

#### Storage Guidelines:

Ideal storage conditions are 60-70°F with relative humidity of 40-50%.

Product performance is warranted for 1 year from date of purchase.

Item No.	Width x Length	Rolls Per Pallet	Stock Item	Application
303036X167	36 IN x 167 LF	94	YES	Underlayment
303036X600	36 IN x 600 LF	32	NO	Packaging
303048X600	48 IN x 600 LF	32	NO	Packaging
303060X600	60 IN x 600 LF	30	NO	Packaging
303072X600	72 IN x 600 LF	30	NO	Packaging
303096X600	96 IN x 600 LF	25	NO	Packaging

Warranty - Holland warrants that Blue Shield 3030 is manufactured with good workmanship, free of defects in material and in compliance with published specifications for a period of 1 year from the date of purchase. Any Blue Shield 3030 product determined to be defective will be replaced at no charge, but in no event is Holland liable of other costs or damages. No other warranties expressed or implied, such as merchantability, fitness of use or other apply. Holland is not liable for any lost in revenue or profit, direct, indirect, special, incidental, or consequential damages.



**MOISTURE  
CONTROL**



**NOISE  
SUPPRESSION**



**Holland  
Manufacturing  
Company**  
Succasunna, NJ  
Corporate HQ  
[www.hollandmfg.com](http://www.hollandmfg.com)