

BLUE SHIELD AS

UNDERLAYMENT FOR WOOD AND TILE FLOORING
VAPOR CONTROL
INDUSTRIAL WRAP



Color: Black
Style: Grade D, Semi-Permeable
Class III Vapor Retarder
Paper: 73.5 lb/rm Kraft
Saturated: 26.5 lb Asphalt
Caliper: 7.0 mils
Tear Str: MD 116 gf CD 164 gf
Permeability: (WVTR), 17.4 perms/119.1 g/day/m²

Water Resistance (AST D-779): PASS

Complete specifications, physical properties, and applicable standards in TDS

Blue Shield Saturated Asphalt Kraft, is a reliable solution that offers a cost-effective method for providing exceptional vapor control in various settings. This material has been a go-to choice for flooring underlayment, ensuring it remains protected from water damage and excessive moisture. Additionally, its versatile nature extends to select small commercial projects, fortifying surfaces and delivering consistent results. Blue Shield Saturated Asphalt is available in various sizes. It not only ensures that surfaces stay in top condition but also guarantees long-term savings and peace of mind.

Product Classification: Semi-permeable Grade D, Class III vapor retardant, asphalt saturated paper

Intended Use: Underlayment for wood flooring

Primary Components: Kraft Paper, Saturating Asphalt

Installation Instructions: **For wood flooring installation:** Holland recommends to following the “Wood Flooring Installation Guidelines” published by NWFA as well as prevailing local building codes. Proper preparation of the installation area is critical including assurance that the sub-floor is dry, level, free of debris and tested for moisture level. Blue Shield AS is not suitable as underlayment for basement and over crawl spaces without additional moisture mitigation steps

Storage Guidelines: Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is warranted for 1 year from date of purchase.

Item No.	Width x Length	Rolls Per Pallet	Stock Item	Application
AS36X144	36 IN x 144 LF	100	YES	Underlayment

Warranty - Holland warrants that Blue Shield AS (Saturated Asphalt) is manufactured with good workmanship, free of defects in material and in compliance with published specifications for a period of 1 year from the date of purchase. Any Blue Shield 3030 product determined to be defective will be replaced at no charge, but in no event is Holland liable of other costs or damages. No other warranties expressed or implied, such as merchantability, fitness of use or other apply. Holland is not liable for any lost in revenue or profit, direct, indirect, special, incidental, or consequential damages.



**MOISTURE
CONTROL**



**NOISE
SUPPRESSION**



**Holland
Manufacturing
Company**
Succasunna, NJ
Corporate HQ
www.hollandmfg.com