

Industrial Kraft Papers



Specification Range

Color: Kraft & Bleached

Basis Weight Range: 40 – 70 lbs/ream

Origin: United States

Width Range: Up to 96"

Roll OD: Max 50", Common 8-9" OD

Core: 2" Coreless



Product Classification: Industrial Kraft Paper – Virgin and Recycled

Intended Use: Voil Fill, Industrial Wrapping, Floor Protection, Surface Protection.

Packaging: Rolls are palletized, stretch wrapped and protected for transit.

Storage Guidelines: Ideal storage conditions are 60-70°F with relative humidity of 40-50%. Product performance is guaranteed for 1 year from date of purchase.

Standard Grades & Sizes:

Grade	Basis Weight (lbs/ream)	Widths	Roll Length	Rolls Per Pallet
Recycled	40	18", 24", 30", 36", 48"	810 LF	18", 24"- 60 Rolls, Other Widths – 30 Rolls
Recycled	50	18", 24", 30", 36", 48"	648 LF	18", 24"- 60 Rolls, Other Widths – 30 Rolls
Virgin	40	18", 24", 30", 36", 48"	810 LF	18", 24"- 60 Rolls, Other Widths – 30 Rolls
Virgin	50	18", 24", 30", 36", 48"	648 LF	18", 24"- 60 Rolls, Other Widths – 30 Rolls

Compliance Statement: Holland's kraft paper products are not intended for direct food contact. Fitness of use of the kraft paper products are at the discretion of the customer.

Warranty: Holland warrants that Industrial Kraft Paper is manufactured with good workmanship, free of defects in material and in compliance with published specifications for a period of 1 year from the date of purchase. Any product determined to be defective will be replaced at no charge, but in no event is Holland liable of other costs or damages. No other warranties expressed or implied, such as merchant- ability, fitness of use or other apply. Holland is not liable for any lost in revenue or profit, direct, indirect, special, incidental, or consequential damages.



Holland Manufacturing Company

Succasunna, NJ – Corporate HQ

www.hollandmfg.com 973-584-8141